

Zebra® card-printer positioning guide



Model	ZXP Series 1	ZXP Series 3	ZXP Series 7	ZXP Series 8	P100i	P330m, P330i & P430i
Quick facts						
Product description	Single-sided colour printer	Single- or double-sided colour printer	Single- or double-sided colour printer	Single- or double-sided colour printer	Single-sided single-feed colour printer	Single- or double-sided colour printer
Printing	Colour dye-sublimation, monochrome thermal transfer	Colour dye-sublimation, monochrome thermal transfer	Colour dye-sublimation, monochrome thermal transfer	Thermal-transfer and dye-diffusion to retransfer film	Colour dye-sublimation, monochrome thermal transfer	Colour dye-sublimation, monochrome thermal transfer
Printer features						
Communications interface	USB, Ethernet (opt.)	USB, Ethernet (opt.)	USB, Ethernet (std.)	USB, Ethernet (std.) 802.11 wireless (option)	USB, Ethernet (opt.)	USB, Ethernet (opt.)
Printing specifications						
Print speed	120 cards per hour single-sided colour. 500 cards per hour monochrome	180 cards per hour single-sided colour. 140 cards per hour double-sided colour. 700 cards per hour monochrome	300 cards per hour single-sided colour. 225 cards per hour double-sided colour. 1375 cards per hour monochrome	190 cards per hour single-sided colour. 180 cards per hour double-sided colour	35 seconds per card colour. 6 seconds per card monochrome	130-140 cards per hour single-sided colour. 102 cards per hour double-sided colour. 286-692 cards per hour monochrome
Edge-to-edge printing	✓	✓	✓	Over-the-edge	✓	✓
Encoder specifications						
UHF Gen 2 RFID encoder	X	X	X	X	X	✓
Three-track magnetic	✓	✓	✓	✓	✓	✓
Smart-card contact	X	✓	✓	✓	✓	✓
MIFARE contactless	X	✓	✓	✓	✓	✓
Smart-card contact station	X	✓	✓	✓	X	✓
Card specifications						
Card Thickness	10-40 mil	10-40 mil	10-50 mil, 30 mil laminated	30-40 mil, 30 mil laminated	20-40 mil	10-60 mil
Card input feeder (card thickness 30 mil/0.762mm)	100 cards	100 cards	200 cards	150 cards	Single card feed	100 cards
Laminator specifications						
Built-in single-system laminator	X	X	✓	✓	X	X

For further information, or to download an electronic copy of this document, please visit [Marketing Store](#).

Use genuine Zebra supplies for the highest reliability and consistency in card printing

Number of images per ribbon roll/cartridge

Model	Monochrome	Colour YMCKO
ZXP Series 1	1,000	100
ZXP Series 3	1,000 & 2,000	200 & 280
ZXP Series 7	2,500 & 5,000	250 & 750
ZXP Series 8	2,500	625
P100i	1,000	200
P330i	1,500	200 & 330
P330m	1,500	-
P430i	1,500	200 & 330

Zebra supplies make it easier than ever to manage your printer

Genuine Zebra supplies meet stringent quality standards, and are recommended for optimal printing quality and proper printer performance. The ZXP Series™ printers are designed to work only with Zebra True Colours® ribbons and Zebra True Secure™ laminates and retransfer film.

For more information, visit www.zebra.com/supplies



Zebra Technologies – EMEA Headquarters & Sales Office
 Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom
Telephone: +44 (0)1628 556000 **Fax:** +44 (0)1628 556001 **Email:** mseurope@zebra.com **Web:** www.zebra.com

Other EMEA Locations
Europe: France, Germany, Italy, the Netherlands, Poland, Russia, Spain, Sweden, Turkey
Middle East & Africa: Dubai, South Africa

©2013 ZIH Corp. i Series, ix Series, True Secure, and all product names and numbers are Zebra trademarks, and Zebra, representation of Zebra Head and True Colours are registered trademarks of ZIH Corp. All rights reserved. MIFARE is a registered trademark of Philips Semiconductors Gratkorn GmbH Ltd. All other trademarks are the property of their respective owners.